




2500 State Road 44 • Oshkosh, WI 54904
 920.231.8222 • FAX 920.231.4666
www.continentalgirbau.com



PowerLoad Plus™

**VENDED 125-POUND CAPACITY
 HARD-MOUNT WASHER-EXTRACTOR**

| | |
|---|--|
| Capacity <i>lbs (kg)</i> | 125 (55) |
| Cylinder Diameter <i>inch (mm)</i> | 42.5 (1080) |
| Cylinder Depth <i>inch (mm)</i> | 23.5 (600) |
| Cylinder Volume <i>cu ft (dm³)</i> | 19.4 (550) |
| Net Weight <i>lbs (kg)</i> | 2426 (1100) |
| Crated Weight <i>lbs (kg)</i> | 2734 (1240) |
| Machine Width <i>inch (mm)</i> | 56 (1422) |
| Machine Depth <i>inch (mm)</i> | 55 (1400) |
| Machine Height <i>inch (mm)</i> | 69 (1745) |
| Door Opening <i>inch (mm)</i> | 21.6 (549) |
| Floor to Door <i>inch (mm)</i> | 24.4 plus base (620) |
| Shipping Dimensions <i>inch (mm)</i> (WxDxH) | 60 x 59 x 77 (1520 x 1490 x 1960) |
| Washing Speed <i>rpm</i> | 34 |
| Spin Speeds <i>rpm</i> | 465 |
| G-force | 130 |
| Static Force Transmitted <i>lbs (kg)</i> | 3080 (1400) |
| Dynamic Force Transmitted <i>lbs (kg)</i> | 5500 (2500) |
| Frequency of Dynamic Force <i>Hz</i> | 7.8 |
| Available Voltages/Wire Conductor/Amp | 208-240/60/3, 3W + G, 40 440/60/3, 3W + G, 25 |
| Drain Diameter <i>inch (mm)</i> | 3 (76) |
| Water Inlets <i>inch (mm)</i> | 1 (25.4) |
| Recommended Water Pressure <i>PSI (bar)</i> | 7-90 (0.5-6) |
| Water Flow <i>gal/min (l/min)</i> | 27 (100) |
| Total Power <i>kW</i> | 3.5 |

| Terminal Connections All Models | | Chemical Injection (Dosing) |
|------------------------------------|---------|----------------------------------|
| Supply # | Conn. # | CM Model Terminal Connections |
| 5 | X5-6 | 47 |
| 4 | X5-5 | 46 |
| 3 | X5-4 | 45 |
| 2 | X5-3 | 44 |
| 1 | X5-2 | 43 |
| Common | X5-1 | 207 |

* Specifications subject to change without notice or obligation.
 Call Continental Girbau, Inc for dimensions not shown or for clarification.

Elevation Base Recommendation:
 2" (50 mm) Steel or Concrete

